

Product HOME-FLEX® Stainless Steel Manifolds

Project Information

Job Name: _____
Location: _____
Engineer: _____
Contractor: _____

Date Submitted: _____
Submitted by: _____
Approved by: _____
Manufacturer's Rep: _____

Installation

Must be installed in accordance with the HOME-FLEX System Design and Installation Guide and all applicable codes

Application Information

Manifolds used for parallel piping installations. May be used in concealed locations on low pressure systems without line pressure regulators

Technical Data

Materials

304-Series Stainless Steel

Pressure Ratings

Specification Operating Pressure

25 PSIG



Temperature Ratings

Operating Temperature Range -20°F - 200°F

Codes

ICC Codes (IFGC, IRC, IMC, IPC), UPC, NFPA (54, 58, 70, 78, 501), CAN/CSA B1491.1, NMC, CMPC, SBCCI, ICC/ANSI 2.0

Standards

ANSI LC1/CSA 6.26, UL 723/ASTM E84, ANSI Z223.1

Listings

CSA 256532, IAPMO 7660

Dimensional Information

	Part Number	OD (Nom. in.)	Length (Nom. in.)	Run Sizes	Port Size (inlet & outlet, NPT)	Port size (middle, NPT)	Weight (lbs)
<input type="checkbox"/>	11-050504	1.75"	10.25"	1/2"	1/2"	1/2"	0.586
<input type="checkbox"/>	11-070504	1.625"	9.875"	1/2", 3/4"	3/4"	1/2"	0.617
<input type="checkbox"/>	11-100704	2.00"	10.375"	3/4", 1"	1"	3/4"	0.75